


Rubber buffers

stainless steel, type E



Material:

Metal parts 1.4401 stainless steel.
Elastomer natural rubber, medium hardness Shore 55A, grey.

Version:

Stainless steel bright.

Sample order:

K1319.00800855

Note:

Rubber buffers are widely-used construction elements for elastic mounting. They are used, among other things, as mountings for aggregates, motors, compressors, pumps and testing machinery.

Temperature range:

-30 °C to +80 °C

On request:

Metal parts 1.4301 stainless steel.

KIPP Rubber buffers, stainless steel, type E

Order No.	D	H	G	T	Spring stiffness N/mm	Load N
K1319.00800855	8	8	M3	3	88	44
K1319.01501255	15	12	M4	4	165	182
K1319.01501555	15	15	M4	4	100	130
K1319.01502055	15	20	M4	4	75	113
K1319.02001555	20	15	M6	5	145	246
K1319.02002055	20	20	M6	5	94	216
K1319.02002555	20	25	M6	5	65	169
K1319.02501555	25	15	M8	7	270	540
K1319.02502555	25	25	M8	7	105	315
K1319.02503055	25	30	M8	7	85	281
K1319.02504055	25	40	M8	7	75	300
K1319.03001555	30	15	M8	7	545	491
K1319.03002555	30	25	M8	7	160	416
K1319.03003055	30	30	M8	7	125	425
K1319.03004055	30	40	M8	7	85	315
K1319.04002055	40	20	M8	7	550	660
K1319.04002555	40	25	M8	7	500	1000
K1319.04003055	40	30	M8	7	300	870
K1319.04004055	40	40	M8	7	260	1040
K1319.05002055	50	20	M10	8	860	860
K1319.05002555	50	25	M10	8	700	1400
K1319.05003055	50	30	M10	8	450	1575
K1319.05004055	50	40	M10	8	350	1400
K1319.05005055	50	50	M10	8	170	850
K1319.06003055	60	30	M10	8	700	1400
K1319.06004055	60	40	M10	8	400	1600
K1319.06005055	60	50	M10	8	240	1200
K1319.07004255	70	42	M10	8	520	2600
K1319.07004555	70	45	M10	8	680	3060
K1319.07502555	75	25	M12	10	1211	1816
K1319.07503055	75	30	M12	10	1090	2289
K1319.07504055	75	40	M12	10	500	2000
K1319.07505055	75	50	M12	10	550	2750