

## Position indicators with stainless steel hollow shaft

### Item description/product images



### Description

#### Material:

Housing polyamide 6.  
Hollow shaft stainless steel.  
Sight glass plastic.  
Grub screw stainless steel.

#### Version:

Housing impact-resistant.  
Hollow shaft and grub screw bright.  
Dial black, digits white.

#### Note:

Position indicators enable the direct reading of set values at a glance. The value indicated per spindle rotation (corresponding spindle pitch) can be selected and the various indicator values are realised by a transmission gear. The position indicators are distinguished by their very clear display and fine scale. They have a torque support that is inserted into a hole on the opposite side.

#### Technical data:

- Counter consisting of 5 10-position dials + fine scale
- Height of figures about 7 mm
- Hollow shaft  $\varnothing$  20 H7 mm
- Temperature resistant to 80 °C
- Oil and solvent resistant
- Dust-proof

#### On request:

- Counter cover made of mineral glass
- Axial sealing (dust-proof)
- Waterproof
- Vibration protection



## Position indicators with stainless steel hollow shaft

### Overview of items

#### Position indicators with stainless steel hollow shaft

Order No.	Main colour	B	D	H	L	Pitch	Decimal point in position	max. rpm	Assembly position	Count direction	Indicator after one rotation
K2108.01001111	orange RAL 2004	38,5	20	67,5	48	1	1	500	1	1	0001,0
K2108.01002111	orange RAL 2004	38,5	20	67,5	48	1	2	500	1	1	000,10
K2108.01001121	orange RAL 2004	38,5	20	67,5	48	1	1	500	1	2	0001,0
K2108.01002121	orange RAL 2004	38,5	20	67,5	48	1	2	500	1	2	000,10
K2108.01001211	orange RAL 2004	38,5	20	67,5	48	1	1	500	2	1	0001,0
K2108.01002211	orange RAL 2004	38,5	20	67,5	48	1	2	500	2	1	000,10
K2108.01001221	orange RAL 2004	38,5	20	67,5	48	1	1	500	2	2	0001,0
K2108.01002221	orange RAL 2004	38,5	20	67,5	48	1	2	500	2	2	000,10
K2108.01001311	orange RAL 2004	38,5	20	67,5	48	1	1	500	3	1	0001,0
K2108.01002311	orange RAL 2004	38,5	20	67,5	48	1	2	500	3	1	000,10
K2108.01001321	orange RAL 2004	38,5	20	67,5	48	1	1	500	3	2	0001,0
K2108.01002321	orange RAL 2004	38,5	20	67,5	48	1	2	500	3	2	000,10
K2108.01001411	orange RAL 2004	38,5	20	67,5	48	1	1	500	4	1	0001,0
K2108.01002411	orange RAL 2004	38,5	20	67,5	48	1	2	500	4	1	000,10
K2108.01001421	orange RAL 2004	38,5	20	67,5	48	1	1	500	4	2	0001,0
K2108.01002421	orange RAL 2004	38,5	20	67,5	48	1	2	500	4	2	000,10
K2108.01501111	orange RAL 2004	38,5	20	67,5	48	1,5	1	500	1	1	0001,5
K2108.01501121	orange RAL 2004	38,5	20	67,5	48	1,5	1	500	1	2	0001,5
K2108.01501211	orange RAL 2004	38,5	20	67,5	48	1,5	1	500	2	1	0001,5
K2108.01501221	orange RAL 2004	38,5	20	67,5	48	1,5	1	500	2	2	0001,5
K2108.01501311	orange RAL 2004	38,5	20	67,5	48	1,5	1	500	3	1	0001,5
K2108.01501321	orange RAL 2004	38,5	20	67,5	48	1,5	1	500	3	2	0001,5
K2108.01501411	orange RAL 2004	38,5	20	67,5	48	1,5	1	500	4	1	0001,5
K2108.01501421	orange RAL 2004	38,5	20	67,5	48	1,5	1	500	4	2	0001,5
K2108.02001111	orange RAL 2004	38,5	20	67,5	48	2	1	500	1	1	0002,0
K2108.02001121	orange RAL 2004	38,5	20	67,5	48	2	1	500	1	2	0002,0
K2108.02001211	orange RAL 2004	38,5	20	67,5	48	2	1	500	2	1	0002,0
K2108.02001221	orange RAL 2004	38,5	20	67,5	48	2	1	500	2	2	0002,0
K2108.02001311	orange RAL 2004	38,5	20	67,5	48	2	1	500	3	1	0002,0
K2108.02001321	orange RAL 2004	38,5	20	67,5	48	2	1	500	3	2	0002,0
K2108.02001411	orange RAL 2004	38,5	20	67,5	48	2	1	500	4	1	0002,0
K2108.02001421	orange RAL 2004	38,5	20	67,5	48	2	1	500	4	2	0002,0
K2108.02501111	orange RAL 2004	38,5	20	67,5	48	2,5	1	500	1	1	0002,5
K2108.02501121	orange RAL 2004	38,5	20	67,5	48	2,5	1	500	1	2	0002,5
K2108.02501211	orange RAL 2004	38,5	20	67,5	48	2,5	1	500	2	1	0002,5
K2108.02501221	orange RAL 2004	38,5	20	67,5	48	2,5	1	500	2	2	0002,5
K2108.02501311	orange RAL 2004	38,5	20	67,5	48	2,5	1	500	3	1	0002,5
K2108.02501321	orange RAL 2004	38,5	20	67,5	48	2,5	1	500	3	2	0002,5
K2108.02501411	orange RAL 2004	38,5	20	67,5	48	2,5	1	500	4	1	0002,5
K2108.02501421	orange RAL 2004	38,5	20	67,5	48	2,5	1	500	4	2	0002,5
K2108.03001111	orange RAL 2004	38,5	20	67,5	48	3	1	500	1	1	0003,0
K2108.03001121	orange RAL 2004	38,5	20	67,5	48	3	1	500	1	2	0003,0
K2108.03001211	orange RAL 2004	38,5	20	67,5	48	3	1	500	2	1	0003,0
K2108.03001221	orange RAL 2004	38,5	20	67,5	48	3	1	500	2	2	0003,0
K2108.03001311	orange RAL 2004	38,5	20	67,5	48	3	1	500	3	1	0003,0
K2108.03001321	orange RAL 2004	38,5	20	67,5	48	3	1	500	3	2	0003,0
K2108.03001411	orange RAL 2004	38,5	20	67,5	48	3	1	500	4	1	0003,0
K2108.03001421	orange RAL 2004	38,5	20	67,5	48	3	1	500	4	2	0003,0
K2108.04001111	orange RAL 2004	38,5	20	67,5	48	4	1	375	1	1	0004,0
K2108.04001121	orange RAL 2004	38,5	20	67,5	48	4	1	375	1	2	0004,0
K2108.04001211	orange RAL 2004	38,5	20	67,5	48	4	1	375	2	1	0004,0
K2108.04001221	orange RAL 2004	38,5	20	67,5	48	4	1	375	2	2	0004,0
K2108.04001311	orange RAL 2004	38,5	20	67,5	48	4	1	375	3	1	0004,0
K2108.04001321	orange RAL 2004	38,5	20	67,5	48	4	1	375	3	2	0004,0
K2108.04001411	orange RAL 2004	38,5	20	67,5	48	4	1	375	4	1	0004,0
K2108.04001421	orange RAL 2004	38,5	20	67,5	48	4	1	375	4	2	0004,0
K2108.05001111	orange RAL 2004	38,5	20	67,5	48	5	1	300	1	1	0005,0
K2108.05001121	orange RAL 2004	38,5	20	67,5	48	5	1	300	1	2	0005,0
K2108.05001211	orange RAL 2004	38,5	20	67,5	48	5	1	300	2	1	0005,0

## Position indicators with stainless steel hollow shaft

### Overview of items

Order No.	Main colour	B	D	H	L	Pitch	Decimal point in position	max. rpm	Assembly position	Count direction	Indicator after one rotation
K2108.05001221	orange RAL 2004	38,5	20	67,5	48	5	1	300	2	2	0005,0
K2108.05001311	orange RAL 2004	38,5	20	67,5	48	5	1	300	3	1	0005,0
K2108.05001321	orange RAL 2004	38,5	20	67,5	48	5	1	300	3	2	0005,0
K2108.05001411	orange RAL 2004	38,5	20	67,5	48	5	1	300	4	1	0005,0
K2108.05001421	orange RAL 2004	38,5	20	67,5	48	5	1	300	4	2	0005,0
K2108.06001111	orange RAL 2004	38,5	20	67,5	48	6	1	250	1	1	0006,0
K2108.06001121	orange RAL 2004	38,5	20	67,5	48	6	1	250	1	2	0006,0
K2108.06001211	orange RAL 2004	38,5	20	67,5	48	6	1	250	2	1	0006,0
K2108.06001221	orange RAL 2004	38,5	20	67,5	48	6	1	250	2	2	0006,0
K2108.06001311	orange RAL 2004	38,5	20	67,5	48	6	1	250	3	1	0006,0
K2108.06001321	orange RAL 2004	38,5	20	67,5	48	6	1	250	3	2	0006,0
K2108.06001411	orange RAL 2004	38,5	20	67,5	48	6	1	250	4	1	0006,0
K2108.06001421	orange RAL 2004	38,5	20	67,5	48	6	1	250	4	2	0006,0
K2108.10001111	orange RAL 2004	38,5	20	67,5	48	10	1	150	1	1	0010,0
K2108.10001121	orange RAL 2004	38,5	20	67,5	48	10	1	150	1	2	0010,0
K2108.10001211	orange RAL 2004	38,5	20	67,5	48	10	1	150	2	1	0010,0
K2108.10001221	orange RAL 2004	38,5	20	67,5	48	10	1	150	2	2	0010,0
K2108.10001311	orange RAL 2004	38,5	20	67,5	48	10	1	150	3	1	0010,0
K2108.10001321	orange RAL 2004	38,5	20	67,5	48	10	1	150	3	2	0010,0
K2108.10001411	orange RAL 2004	38,5	20	67,5	48	10	1	150	4	1	0010,0
K2108.10001421	orange RAL 2004	38,5	20	67,5	48	10	1	150	4	2	0010,0
K2108.01001112	black	38,5	20	67,5	48	1	1	500	1	1	0001,0
K2108.01002112	black	38,5	20	67,5	48	1	2	500	1	1	000,10
K2108.01001122	black	38,5	20	67,5	48	1	1	500	1	2	0001,0
K2108.01002122	black	38,5	20	67,5	48	1	2	500	1	2	000,10
K2108.01001212	black	38,5	20	67,5	48	1	1	500	2	1	0001,0
K2108.01002212	black	38,5	20	67,5	48	1	2	500	2	1	000,10
K2108.01001222	black	38,5	20	67,5	48	1	1	500	2	2	0001,0
K2108.01002222	black	38,5	20	67,5	48	1	2	500	2	2	000,10
K2108.01001312	black	38,5	20	67,5	48	1	1	500	3	1	0001,0
K2108.01002312	black	38,5	20	67,5	48	1	2	500	3	1	000,10
K2108.01001322	black	38,5	20	67,5	48	1	1	500	3	2	0001,0
K2108.01002322	black	38,5	20	67,5	48	1	2	500	3	2	000,10
K2108.01001412	black	38,5	20	67,5	48	1	1	500	4	1	0001,0
K2108.01002412	black	38,5	20	67,5	48	1	2	500	4	1	000,10
K2108.01001422	black	38,5	20	67,5	48	1	1	500	4	2	0001,0
K2108.01002422	black	38,5	20	67,5	48	1	2	500	4	2	000,10
K2108.01501112	black	38,5	20	67,5	48	1,5	1	500	1	1	0001,5
K2108.01501122	black	38,5	20	67,5	48	1,5	1	500	1	2	0001,5
K2108.01501212	black	38,5	20	67,5	48	1,5	1	500	2	1	0001,5
K2108.01501222	black	38,5	20	67,5	48	1,5	1	500	2	2	0001,5
K2108.01501312	black	38,5	20	67,5	48	1,5	1	500	3	1	0001,5
K2108.01501322	black	38,5	20	67,5	48	1,5	1	500	3	2	0001,5
K2108.01501412	black	38,5	20	67,5	48	1,5	1	500	4	1	0001,5
K2108.01501422	black	38,5	20	67,5	48	1,5	1	500	4	2	0001,5
K2108.02001112	black	38,5	20	67,5	48	2	1	500	1	1	0002,0
K2108.02001122	black	38,5	20	67,5	48	2	1	500	1	2	0002,0
K2108.02001212	black	38,5	20	67,5	48	2	1	500	2	1	0002,0
K2108.02001222	black	38,5	20	67,5	48	2	1	500	2	2	0002,0
K2108.02001312	black	38,5	20	67,5	48	2	1	500	3	1	0002,0
K2108.02001322	black	38,5	20	67,5	48	2	1	500	3	2	0002,0
K2108.02001412	black	38,5	20	67,5	48	2	1	500	4	1	0002,0
K2108.02001422	black	38,5	20	67,5	48	2	1	500	4	2	0002,0
K2108.02501112	black	38,5	20	67,5	48	2,5	1	500	1	1	0002,5
K2108.02501122	black	38,5	20	67,5	48	2,5	1	500	1	2	0002,5
K2108.02501212	black	38,5	20	67,5	48	2,5	1	500	2	1	0002,5
K2108.02501222	black	38,5	20	67,5	48	2,5	1	500	2	2	0002,5
K2108.02501312	black	38,5	20	67,5	48	2,5	1	500	3	1	0002,5
K2108.02501322	black	38,5	20	67,5	48	2,5	1	500	3	2	0002,5
K2108.02501412	black	38,5	20	67,5	48	2,5	1	500	4	1	0002,5
K2108.02501422	black	38,5	20	67,5	48	2,5	1	500	4	2	0002,5

## Position indicators with stainless steel hollow shaft

### Overview of items

Order No.	Main colour	B	D	H	L	Pitch	Decimal point in position	max. rpm	Assembly position	Count direction	Indicator after one rotation
K2108.03001112	black	38,5	20	67,5	48	3	1	500	1	1	0003,0
K2108.03001122	black	38,5	20	67,5	48	3	1	500	1	2	0003,0
K2108.03001212	black	38,5	20	67,5	48	3	1	500	2	1	0003,0
K2108.03001222	black	38,5	20	67,5	48	3	1	500	2	2	0003,0
K2108.03001312	black	38,5	20	67,5	48	3	1	500	3	1	0003,0
K2108.03001322	black	38,5	20	67,5	48	3	1	500	3	2	0003,0
K2108.03001412	black	38,5	20	67,5	48	3	1	500	4	1	0003,0
K2108.03001422	black	38,5	20	67,5	48	3	1	500	4	2	0003,0
K2108.04001112	black	38,5	20	67,5	48	4	1	375	1	1	0004,0
K2108.04001122	black	38,5	20	67,5	48	4	1	375	1	2	0004,0
K2108.04001212	black	38,5	20	67,5	48	4	1	375	2	1	0004,0
K2108.04001222	black	38,5	20	67,5	48	4	1	375	2	2	0004,0
K2108.04001312	black	38,5	20	67,5	48	4	1	375	3	1	0004,0
K2108.04001322	black	38,5	20	67,5	48	4	1	375	3	2	0004,0
K2108.04001412	black	38,5	20	67,5	48	4	1	375	4	1	0004,0
K2108.04001422	black	38,5	20	67,5	48	4	1	375	4	2	0004,0
K2108.05001112	black	38,5	20	67,5	48	5	1	300	1	1	0005,0
K2108.05001122	black	38,5	20	67,5	48	5	1	300	1	2	0005,0
K2108.05001212	black	38,5	20	67,5	48	5	1	300	2	1	0005,0
K2108.05001222	black	38,5	20	67,5	48	5	1	300	2	2	0005,0
K2108.05001312	black	38,5	20	67,5	48	5	1	300	3	1	0005,0
K2108.05001322	black	38,5	20	67,5	48	5	1	300	3	2	0005,0
K2108.05001412	black	38,5	20	67,5	48	5	1	300	4	1	0005,0
K2108.05001422	black	38,5	20	67,5	48	5	1	300	4	2	0005,0
K2108.06001112	black	38,5	20	67,5	48	6	1	250	1	1	0006,0
K2108.06001122	black	38,5	20	67,5	48	6	1	250	1	2	0006,0
K2108.06001212	black	38,5	20	67,5	48	6	1	250	2	1	0006,0
K2108.06001222	black	38,5	20	67,5	48	6	1	250	2	2	0006,0
K2108.06001312	black	38,5	20	67,5	48	6	1	250	3	1	0006,0
K2108.06001322	black	38,5	20	67,5	48	6	1	250	3	2	0006,0
K2108.06001412	black	38,5	20	67,5	48	6	1	250	4	1	0006,0
K2108.06001422	black	38,5	20	67,5	48	6	1	250	4	2	0006,0
K2108.10001112	black	38,5	20	67,5	48	10	1	150	1	1	0010,0
K2108.10001122	black	38,5	20	67,5	48	10	1	150	1	2	0010,0
K2108.10001212	black	38,5	20	67,5	48	10	1	150	2	1	0010,0
K2108.10001222	black	38,5	20	67,5	48	10	1	150	2	2	0010,0
K2108.10001312	black	38,5	20	67,5	48	10	1	150	3	1	0010,0
K2108.10001322	black	38,5	20	67,5	48	10	1	150	3	2	0010,0
K2108.10001412	black	38,5	20	67,5	48	10	1	150	4	1	0010,0
K2108.10001422	black	38,5	20	67,5	48	10	1	150	4	2	0010,0