

Elastomer buffers

Shore 70A



Material:

Polyurethane.

Version:

Soft Shore hardness 70A ±5.

Colour black.

Sample order:

nIm 26090-02001670

Note:


Elastomer buffers are characterised by high load capacity, long service life and high economy due to being entirely maintenance-free. They also provide outstanding protection for persons and machines since the buffers do not rupture when overloaded.

They are used to insulate and dampen air and structure-borne sound and offer progressive buffering characteristics with sustained excellent performance.

They are also resistant to grease and oils and, in terms of performance and quality fulfil the requirements of the standard ISO 10069-1.

Temperature range:

-20 °C to +80 °C.



Order No.	D	D1	L0
26090-01601270	16	6,5	12,5
26090-01601670	16	6,5	16
26090-01602070	16	6,5	20
26090-01602570	16	6,5	25
26090-02001670	20	8,5	16
26090-02002070	20	8,5	20
26090-02002570	20	8,5	25
26090-02003270	20	8,5	32
26090-02502070	25	10,5	20
26090-02502570	25	10,5	25
26090-02503270	25	10,5	32
26090-02504070	25	10,5	40
26090-03203270	32	13,5	32
26090-03204070	32	13,5	40
26090-03205070	32	13,5	50
26090-03206370	32	13,5	63
26090-05003270	50	17	32
26090-05004070	50	17	40
26090-05005070	50	17	50
26090-05006370	50	17	63
26090-05008070	50	17	80
26090-05010070	50	17	100
26090-10003270	100	21	32
26090-10004070	100	21	40
26090-10005070	100	21	50
26090-10006370	100	21	63
26090-10008070	100	21	80
26090-10010070	100	21	100
26090-10012570	100	21	125