

Elastomer buffers

Shore 80A



Material:

Polyurethane.

Version:

Medium Shore hardness 80A ±5.

Colour yellow.

Sample order:

nIm 26091-01601280

Note:


Elastomer buffers are characterised by high load capacity, long service life and high economy due to being entirely maintenance-free. They also provide outstanding protection for persons and machines since the buffers do not rupture when overloaded.

They are used to insulate and dampen air and structure-borne sound and offer progressive buffering characteristics with sustained excellent performance.

They are also resistant to grease and oils and, in terms of performance and quality fulfil the requirements of the standard ISO 10069-1.

Temperature range:

-20 °C to +80 °C.



Order No.	D	D1	L0
26091-01601280	16	6,5	12,5
26091-01601680	16	6,5	16
26091-01602080	16	6,5	20
26091-01602580	16	6,5	25
26091-02001680	20	8,5	16
26091-02002080	20	8,5	20
26091-02002580	20	8,5	25
26091-02003280	20	8,5	32
26091-02502080	25	10,5	20
26091-02502580	25	10,5	25
26091-02503280	25	10,5	32
26091-02504080	25	10,5	40
26091-03203280	32	13,5	32
26091-03204080	32	13,5	40
26091-03205080	32	13,5	50
26091-03206380	32	13,5	63
26091-05003280	50	17	32
26091-05004080	50	17	40
26091-05005080	50	17	50
26091-05006380	50	17	63
26091-05008080	50	17	80
26091-05010080	50	17	100
26091-10003280	100	21	32
26091-10004080	100	21	40
26091-10005080	100	21	50
26091-10006380	100	21	63
26091-10008080	100	21	80
26091-10010080	100	21	100
26091-10012580	100	21	125