


Grease nipples

button head DIN 3404



Material:

Steel or 1.4305 stainless steel

Version:

Steel electro zinc-plated.
Stainless steel bright.

Sample order:

nIm 97944-11006100

Note:

As the construction of button head grease nipples allow for a high lubrication flow rate, they are especially useful for lubrication points which require a large grease volume. Because of the robust design, button head grease nipples are preferred for machines that are subjected to high external stress.

Order No.	Main material	D	D1	L	L1	SW
97944-11006100	steel	M6x1	10	13,5	5,5	11
97944-11008100	steel	M8x1	10	13,5	5,5	11
97944-11010100	steel	M10x1	10	13,5	5,5	11
97944-11018	steel	G1/8	10	13,5	5,5	11
97944-11606100	steel	M6x1	16	17	6	17
97944-11608100	steel	M8x1	16	17	6	17
97944-11608125	steel	M8x1,25	16	17	6	17
97944-11610100	steel	M10x1	16	17	6	17
97944-11610150	steel	M10x1,5	16	17	6	17
97944-11612150	steel	M12x1,5	16	17	6	17
97944-11616150	steel	M16x1,5	16	18	7	17
97944-11618	steel	G1/8	16	17	6	17
97944-11614	steel	G1/4	16	17	6	17
97944-12216150	steel	M16x1,5	22	21,5	8	22
97944-12214	steel	G1/4	22	21,5	8	22
97944-12238	steel	G3/8	22	21,5	8	22
97944-21606100	stainless steel	M6x1	16	17	6	17
97944-21608100	stainless steel	M8x1	16	17	6	17
97944-21608125	stainless steel	M8x1,25	16	17	6	17
97944-21610100	stainless steel	M10x1	16	17	6	17
97944-21610150	stainless steel	M10x1,5	16	17	6	17
97944-21612150	stainless steel	M12x1,5	16	17	6	17
97944-21618	stainless steel	G1/8	16	17	6	17
97944-21614	stainless steel	G1/4	16	17	6	17
97944-22216150	stainless steel	M16x1,5	22	21,5	8	22
97944-22214	stainless steel	G1/4	22	21,5	8	22
97944-22238	stainless steel	G3/8	22	21,5	8	22