

DISTRIBUTIONAL LOGISTICS




Etage

The ideal solution





FEATURES







DISTRIBUTIONAL LOGISTICS

Etage

The ideal solution

- loading capacity Bottom: max. 300 kg
- loading capacity per shelf: max. 100 kg
- Total loading capacity with shelves: max. 500 kg
- including two intermediate shelves
- torsionally flexible and highly resistant blue plastic bottom
- safety skids for fork lift loading
- central lock with foot-operated lever
- high stability when loading and unloading
- pulling handle with handbrake
- truck compatible loading dimensions
- · 2 stable end panels with 3 pairs of web lashings each on the long sides
- can be moved together using optional coupling and drawbar system

Dimensions outside (I x w x h in mm):

1200 x 590 x 1600

Dimensions inside (I x w x h in mm):

1200 x 590 x 1600

optional:

coupling and drawbar

serial running gear:

- 2 swivel castors and 2 fixed castors as elastic solid rubber tyres, do not leave marks, ø 160 mm
- swivel castors with integrated central stop
- all castors with double ball bearing in the ring mount and ball bearing in the wheel hub
- Hardness: 65° Shore A
- Wheel guards on all castors

| Туре | Art. no. |
|-----------------------|-------------|
| Ecoflex Etage, with 1 | 190-0007 |
| shelf | |
| Ecoflex Etage, with 2 | 190-0010 |
| shelves | |
| coupling | 194-5000-S2 |
| drawbar | 194-6000-S |

FURTHER PRODUCTS



Letter tray trolley Ecoflex BATCH



Commissioner



Motor



Letter tray trolley Ecoflex Standard