


Profile

- Resolution max. 5000 pulses/revolution
- Through hollow shaft up to max. $\varnothing 28$ mm
- M12 or cable connection



Mechanical data

Feature	Technical data	Additional information
Shaft	steel	
Housing	aluminum	
Speed	≤ 2500 rpm	
Moment of inertia	$\sim 3.5 \times 10^{-6} \text{ kgm}^2$	
Starting torque	$< 0.1 \text{ Nm}$ at 20 °C	
Cable sheath	PVC	$\varnothing 4.5$ mm
Cable bending radius	27 mm	static
	68 mm	dynamic
Weight	~ 0.4 kg	

Electrical data

■ OP output circuit

Feature	Technical data	Additional information
Operating voltage	8 ... 30 V DC	reverse-polarity protected
Current consumption	typical 40 mA	≤100 mA (no load)
Output signal level high	≥UB - 3.0 V	short-circuit proof
Output signal level low	≤2.5 V	short-circuit proof
Pulse frequency	≤200 kHz	
Load	±40 mA	max. adm.
Type of connection	open cable end 1x M12 connector	8-pole, 1x pin


■ LD5 output circuit

Feature	Technical data	Additional information
Operating voltage	5 V DC	reverse-polarity protected
Current consumption	typical 40 mA	≤90 mA (no load)
Output signal level high	≥2.5 V	short-circuit proof
Output signal level low	≤0.5 V	short-circuit proof
Pulse frequency	≤300 kHz	
Load	±20 mA	max. adm.
Type of connection	open cable end 1x M12 connector	8-pole, 1x pin

■ LD24 output circuit

Feature	Technical data	Additional information
Operating voltage	8 ... 30 V DC	reverse-polarity protected
Current consumption	typical 40 mA	≤90 mA (no load)
Output signal level high	≥2.5 V	short-circuit proof
Output signal level low	≤0.5 V	short-circuit proof
Pulse frequency	≤300 kHz	
Load	±20 mA	max. adm.
Type of connection	open cable end 1x M12 connector	8-pole, 1x pin

■ signal pattern



Ambient conditions

Feature	Technical data	Additional information
Ambient temperature	-20 ... 70 °C -20 ... 60 °C	at speed ≤2000 min ⁻¹ at speed ≤2500 min ⁻¹
EMC	EN 61000-6-2 EN 61000-6-3	interference resistance / immission emitted interference / emission
Protection category	IP64	EN 60529
Shock resistance	1000 m/s ² , 6 ms	EN 60068-2-27
Vibration resistance	100 m/s ² , 35 ... 2000 Hz	EN 60068-2-6

Pin assignment

Signal	E1	E12
GND	white	1
+UB	brown	2
A	green	3
/A	yellow	4
B	gray	5
/B	pink	6
0	blue	7
/0	red	8

Order

Ordering table

Feature	Ordering data	Specification	Additional information
Pulses/revolution	... A	50, 100, 125, 250, 400, 500, 512, 1000, 1024, 2000, 2048, 5000	
Type of connection	E1 B E12	open cable ends plug	
Cable length	... C OK	01.0 in m without	only with E1 only with E12
Output circuit	OP D LD5 LD24	Push-pull with inversion LineDriver, 5 V LineDriver, 8 ... 30 V	
Hollow shaft/diameter	... E	16, 20, 24, 28 in mm	

Order key

IH5828 - ABO - A - B - C - D - E

Scope of delivery: IH5828, Quick Start Guide

Accessories:

Electronic display MA10/4
Electronic display MA48
Electronic display MA55
Cable extension KV08S2
Mating Connector Overview
Mating connector, 8-pole, socket

www.siko-global.com
www.siko-global.com
www.siko-global.com
www.siko-global.com
www.siko-global.com
Order key 83525