

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 14

SDS No.: 173280

V005.4

Revision: 23.03.2016 printing date: 06.09.2016

Replaces version from: 21.04.2015

LOCTITE SF 7386 ACTIVATOR known as 7386 500ML BTL X 6 EN/CH/JP

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 7386 ACTIVATOR known as 7386 500ML BTL X 6 EN/CH/JP

Contains:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Diethyl-phenyl-propyl-dihydropyridine

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

activator

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids Category 2

H225 Highly flammable liquid and vapor.

Acute toxicity Category 4

H302 Harmful if swallowed. Route of Exposure: Oral

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure Category 3

H336 May cause drowsiness or dizziness.

Target organ: Central Nervous System

Aspiration hazard Category 1

H304 May be fatal if swallowed and enters airways.

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

EN/CH/JP

2.2. Label elements

MSDS-No.: 173280

Label elements (CLP):

Hazard pictogram:



Signal word: Danger

Hazard statement: H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation. H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: ***For consumer use only: P101 If medical advice is needed, have product container or

label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in

accordance with local authority requirements***

Precautionary statement: P210 Keep away from heat/open flames/hot surfaces. - No smoking.

P261 Avoid breathing vapours. Prevention

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor. **Precautionary statement:**

P331 Do NOT induce vomiting. Response

P302+P352 IF ON SKIN: Wash with plenty of water.

P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Solvent based activator.

Page 3 of 14

MSDS-No.: 173280 V005.4

EN/CH/JP

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Hydrocarbons, C7, n-alkanes, isoalkanes,	300-230-4	50- < 75 %	Asp. Tox. 1
cyclics	01-2119475515-33		H304
93924-37-9			Skin Irrit. 2
			H315
			Flam. Liq. 2
			H225
			STOT SE 3; Inhalation
			H336
			Aquatic Chronic 2
			H411
Diethyl-phenyl-propyl-dihydropyridine	252-091-3	25-< 50 %	Acute Tox. 4; Oral
34562-31-7			H302
			Acute Tox. 4; Dermal
			H312
			Skin Irrit. 2; Dermal
			H315
			Eye Irrit. 2
			H319
			Aquatic Chronic 4
			H413
Propan-2-ol	200-661-7	10- < 25 %	Flam. Liq. 2
67-63-0	01-2119457558-25		H225
0, 00 0	2217.07000 20		Eye Irrit. 2
			H319
			STOT SE 3
			H336
			1100
	1		

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air.

Seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

ASPIRATION: Coughing, shortness of breath, nausea. Delayed effect: bronchopneumonia or pulmonary oedema

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

INGESTION: Nausea, vomiting, diarrhea, abdominal pain.

Vapors may cause drowsiness and dizziness.

V005.4 EN/CH/JP

MSDS-No.: 173280 Page 4 of 14

4.3. Indication of any immediate medical attention and special treatment needed

Swallowing may cause irritation of mouth, throat and digestive tract, diarrhea and vomiting

Do not induce vomiting.

Seek medical attention from a specialist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

5.2. Special hazards arising from the substance or mixture

Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

Wipe up using absorbent material.

Store in a partly filled, closed container until disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from sources of ignition - no smoking.

Vapours should be extracted to avoid inhalation.

Use only in well-ventilated areas.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry place.

Do not store near sources of heat or ignition, or reactive materials.

7.3. Specific end use(s)

activator

EN/CH/JP

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Propan-2-ol 67-63-0 [PROPAN-2-OL]	500	1.250	Short Term Exposure Limit (STEL):		EH40 WEL
Propan-2-ol 67-63-0 [PROPAN-2-OL]	400	999	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit	Regulatory list
				category / Remarks	
Propan-2-ol	400		Short Term Exposure		IR_OEL
67-63-0			Limit (STEL):		
[ISOPROPYL ALCOHOL]					
Propan-2-ol	200		Time Weighted Average		IR_OEL
67-63-0			(TWA):		
[ISOPROPYL ALCOHOL]					
Propan-2-ol			Skin designation:	Can be absorbed through the	IR_OEL
67-63-0				skin.	
[ISOPROPYL ALCOHOL]					

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period					Remarks
			mg/l	ppm	mg/kg	others	
Propan-2-ol 67-63-0	aqua (freshwater)					140,9 mg/L	
Propan-2-ol 67-63-0	aqua (marine water)					140,9 mg/L	
Propan-2-ol 67-63-0	sediment (freshwater)				552 mg/kg		
Propan-2-ol 67-63-0	sediment (marine water)				552 mg/kg		
Propan-2-ol 67-63-0	soil				28 mg/kg		
Propan-2-ol 67-63-0	aqua (intermittent releases)					140,9 mg/L	
Propan-2-ol 67-63-0	sewage treatment plant (STP)					2251 mg/L	
Propan-2-ol 67-63-0	oral					160 mg/kg food	

Page 6 of 14

Derived No-Effect Level (DNEL):

Name on list	Application	Route of	Health Effect	Exposure	Value	Remarks
	Area	Exposure		Time		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Workers	dermal	Long term exposure -		300 mg/kg bw/day	
93924-37-9			systemic effects			
Hydrocarbons, C7, n-alkanes, isoalkanes,	Workers	Inhalation	Long term		2085 mg/m3	
cyclics 93924-37-9			exposure - systemic effects			
Hydrocarbons, C7, n-alkanes, isoalkanes,	general	dermal	Long term		149 mg/kg bw/day	
cyclics 93924-37-9	population		exposure - systemic effects			
Hydrocarbons, C7, n-alkanes, isoalkanes,	general	oral	Long term		149 mg/kg bw/day	
cyclics 93924-37-9	population		exposure - systemic effects			
Hydrocarbons, C7, n-alkanes, isoalkanes,	general	Inhalation	Long term		477 mg/m3	
cyclics 93924-37-9	population		exposure - systemic effects			
Propan-2-ol	Workers	dermal	Long term		888 mg/kg bw/day	
67-63-0			exposure - systemic effects			
Propan-2-ol	Workers	inhalation	Long term		500 mg/m3	
67-63-0			exposure - systemic effects			
Propan-2-ol	general	dermal	Long term		319 mg/kg bw/day	
67-63-0	population		exposure - systemic effects			
Propan-2-ol	general	inhalation	Long term		89 mg/m3	
67-63-0	population		exposure - systemic effects			
Propan-2-ol	general	oral	Long term		26 mg/kg bw/day	
67-63-0	population		exposure - systemic effects			
		l	systemic effects	l		

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Do not inhale vapors and fumes.

Use only in well-ventilated areas.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

LOCTITE SF 7386 ACTIVATOR known as 7386 500ML BTL X 6

Page 7 of 14

V005.4 EN/CH/JP

Skin protection:

MSDS-No.: 173280

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid

clear

yellow, Amber, greenish

Odor Aliphatic

Odour threshold No data available / Not applicable

pH Not applicable Initial boiling point $82 \,^{\circ}\text{C} (179.6 \,^{\circ}\text{F})$ Flash point $-5 \,^{\circ}\text{C} (23 \,^{\circ}\text{F})$

Decomposition temperature No data available / Not applicable

Vapour pressure 35 mm hg

(20 °C (68 °F))

Density 0,8 g/cm³

()

Bulk density
No data available / Not applicable
Viscosity
No data available / Not applicable
Viscosity (kinematic)
No data available / Not applicable
Explosive properties
No data available / Not applicable

Solubility (qualitative) Insoluble

Solidification temperature

Mo data available / Not applicable
Melting point

No data available / Not applicable
Not at available / Not applicable
Not at available / Not applicable
Not at available / Not applicable
Auto-ignition temperature

No data available / Not applicable
Explosive limits

No data available / Not applicable
Partition coefficient: n-octanol/water

No data available / Not applicable
Evaporation rate

No data available / Not applicable

Vapor density Heavier than air

Oxidising properties No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Strong oxidizing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications. Heat, flames, sparks and other sources of ignition.

EN/CH/JP

Page 8 of 14

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

Harmful if swallowed.

May be fatal if swallowed and enters airways.

Inhalative toxicity:

May cause headache and dizziness.

Skin irritation:

Causes skin irritation.

Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals.

Eye irritation:

Causes serious eye irritation.

Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Hydrocarbons, C7, n-	LD50	> 5.840 mg/kg	oral		rat	OECD Guideline 401 (Acute
alkanes, isoalkanes,						Oral Toxicity)
cyclics						
93924-37-9						
Propan-2-ol	LD50	5.840 mg/kg	oral		rat	OECD Guideline 401 (Acute
67-63-0						Oral Toxicity)

Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 93924-37-9	LC50	> 23,3 mg/l	vapour		rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Propan-2-ol 67-63-0	LC50	72,6 mg/l		4 h	rat	

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 93924-37-9	LD50	> 2.920 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)
Propan-2-ol 67-63-0	LD50	12.870 mg/kg	dermal		rabbit	

Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Diethyl-phenyl-propyl-	irritating			
dihydropyridine 34562-31-7				
Propan-2-ol	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute
I	Slightly irritating	411	labolt	`
67-63-0				Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Diethyl-phenyl-propyl- dihydropyridine	irritating			
34562-31-7				
Propan-2-ol	moderately irritating		rabbit	OECD Guideline 405 (Acute
67-63-0				Eye Irritation / Corrosion)

${\bf Respiratory\ or\ skin\ sensitization:}$

Hazardous components CAS-No.	Result	Test type	Species	Method
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Propan-2-ol 67-63-0	metabolic	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene
	activation				Mutation Test)
Propan-2-ol	negative	intraperitoneal		mouse	OECD Guideline 474
67-63-0					(Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity:

Hazardous components CAS-No.	Result	Species	Sex	Exposure timeFrequenc y of treatment	Route of application	Method
Propan-2-ol		rat	male/female	104 w	inhalation:	OECD Guideline 451
67-63-0				6 h/d, 5 d/w	vapour	(Carcinogenicity Studies)

Reproductive toxicity:

Hazardous substances	Result / Classification	Species	Exposure	Species	Method
Propan-2-ol 67-63-0	NOAEL P = 853 mg/kg	One generation study oral: drinking water	time	rat	OECD Guideline 415 (One- Generation Reproduction Toxicity Study)
	NOAEL P = 500 mg/kg NOAEL F1 = 1.000 mg/kg	Two generation study oral: gavage		rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Propan-2-ol 67-63-0		inhalation: vapour	at least 104 w6 h/d, 5 d/w	rat	

EN/CH/JP

SECTION 12: Ecological information

General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity

Ecotoxicity:

Toxic to aquatic life with long lasting effects.

Do not empty into drains / surface water / ground water.

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity	time		
			Study			
Hydrocarbons, C7, n-alkanes,	EC50	3 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
isoalkanes, cyclics						202 (Daphnia sp.
93924-37-9						Acute
						Immobilisation
						Test)
Hydrocarbons, C7, n-alkanes,	NOEC	0,17 mg/l	chronic	21 d	Daphnia magna	OECD 211
isoalkanes, cyclics			Daphnia			(Daphnia magna,
93924-37-9						Reproduction Test)
Propan-2-ol	LC50	> 9.640 - 10.000 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline
67-63-0						203 (Fish, Acute
						Toxicity Test)
Propan-2-ol	EC50	> 1.000 mg/l	Algae	96 h	Scenedesmus subspicatus (new	OECD Guideline
67-63-0					name: Desmodesmus	201 (Alga, Growth
					subspicatus)	Inhibition Test)
	NOEC	1.000 mg/l	Algae	96 h	Scenedesmus subspicatus (new	OECD Guideline
					name: Desmodesmus	201 (Alga, Growth
					subspicatus)	Inhibition Test)
Propan-2-ol	EC 50	> 1.000 mg/l	Bacteria	3 h		OECD Guideline
67-63-0						209 (Activated
						Sludge, Respiration
						Inhibition Test)
Propan-2-ol	NOEC	30 mg/l	chronic	21 d	Daphnia magna	OECD 211
67-63-0			Daphnia			(Daphnia magna,
			_			Reproduction Test)

12.2. Persistence and degradability

Persistence and Biodegradability:

No data available.

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		
Hydrocarbons, C7, n-alkanes,	readily biodegradable	aerobic	98 %	OECD Guideline 301 F (Ready
isoalkanes, cyclics				Biodegradability: Manometric
93924-37-9				Respirometry Test)
Propan-2-ol	readily biodegradable	aerobic	70 - 84 %	EU Method C.4-E (Determination
67-63-0				of the "Ready"
				BiodegradabilityClosed Bottle
				Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Mobility:

The product evaporates readily.

Bioaccumulative potential:

No data available.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Propan-2-ol 67-63-0	0,05					OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake
						Flask Method)

Page 11 of 14

MSDS-No.: 173280 V005.4

EN/CH/JP

12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
Hydrocarbons, C7, n-alkanes, isoalkanes,	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
cyclics	Bioaccumulative (vPvB) criteria.
93924-37-9	
Propan-2-ol	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
67-63-0	Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of according to regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

14 06 03 - other solvents and solvent mixtures

LOCTITE SF 7386 ACTIVATOR known as 7386 500ML BTL X $6\,$

Page 12 of 14

EN/CH/JP

SECTION 14: Transport information

14.1. UN number

MSDS-No.: 173280

V005.4

ADR	1993
RID	1993
ADN	1993
IMDG	1993
IATA	1993

14.2. UN proper shipping name

ADR	FLAMMABLE LIQUID, N.O.S. (Heptanes, Isopropanol)
RID	FLAMMABLE LIQUID, N.O.S. (Heptanes, Isopropanol)
ADN	FLAMMABLE LIQUID, N.O.S. (Heptanes, Isopropanol)
IMDG	FLAMMABLE LIQUID, N.O.S. (Heptanes, Isopropanol)
IATA	Flammable liquid, n.o.s. (Heptanes, Isopropanol)

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
ΙΔΤΔ	II

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous

IMDG Marine pollutant IATA not applicable

14.6. Special precautions for user

ADR	Special provision 640D
	Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

Page 13 of 14

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Label elements (DPD):

F - Highly flammable



Xn - Harmful



N - Dangerous for the environment



Risk phrases:

R11 Highly flammable.

R21/22 Harmful in contact with skin and if swallowed.

R36/38 Irritating to eyes and skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

Safety phrases:

S16 Keep away from sources of ignition - No smoking.

 $S23\ Do\ not\ breathe\ vapour.$

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of water and soap.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Additional labeling:

For consumer use only: S2 Keep out of the reach of children.

S46 If swallowed, seek medical advice immediately and show this container or label.

LOCTITE SF 7386 ACTIVATOR known as 7386 500ML BTL X 6 $\,$

MSDS-No.: 173280 Page 14 of 14 V005.4 EN/CH/JP

Contains:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Diethyl-phenyl-propyl-dihydropyridine

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.