



# STAINLESS STEEL BEARING ROLLER (HEAVY DUTY/L-SHAPE)



## JS315



- L-shaped roller.
- Sealed bearing ideal for outdoor environment.
- Bracket has holes for fasteners or it also can be welded.



Item No.	Load Capacity (kg/2pcs)	D	D <sub>1</sub>	W	W <sub>1</sub>	A	B	C	E
JS315-100L	1500 (3300 lbs)	120 (4-23/32")	100 (3-15/16")	36 (1-27/64")	70 ( 2-3/4" )	145 ( 5-45/64" )	46 (1-13/16")	27.0 ( 1-1/16" )	9.0 (23/64")
JS315-150L	2200 (4840 lbs)	150 (5-29/32")	130 ( 5-1/8" )	43 (1-11/16")	88 (3-15/32")	250 ( 9-27/32" )	57 ( 2-1/4" )	33.0 (1-19/64")	10.0 (25/64")
JS315-200L	2800 (6160 lbs)	200 ( 7-7/8" )	170 (6-11/16")	50 (1-31/32")	96 (3-25/32")	290 (11-27/64")	70 ( 2-3/4" )	36.5 ( 1-1/16" )	13.5 (17/32")

Item No.	F	H	H <sub>1</sub>	H <sub>2</sub>	d	I	P	t	Weight (kg)
JS315-100L	10 (25/64")	124 ( 4-7/8" )	114 (4-31/64")	87 (3-27/64")	11 ( 7/16" )	15 (19/32")	115 (4-17/32")	3 ( 1/8" )	3.0
JS315-150L		165 ( 6-1/2" )	155 ( 6-7/64" )	137 (5-25/64")			185 ( 7-9/32" )	4 ( 5/32" )	6.8
JS315-200L	15 (19/32")	215 (8-15/32")	200 ( 7-7/8" )	160 (6-19/64")	20 (25/32")	35 (1-3/8")	216 ( 8-1/2" )	6 (15/64")	13.4



# STAINLESS STEEL ROLLER (HEAVY DUTY/L-SHAPE)



## JS325



- L-shaped roller wheel for JS315.
- Sealed bearing ideal for outdoor environment.



\*Measurement includes spring washer thickness

Item No.	D	D <sub>1</sub>	A	B	C	E
JS325-100L	120 (4-23/32")	100 (3-15/16")	40 ( 37/64" )	36 (1-27/64")	27.0 ( 1-1/16" )	9.0 (23/64")
JS325-150L	150 (5-29/32")	130 ( 5-1/8" )	*43 (1-11/16")	43 (1-11/16")	33.0 (1-19/64")	10.0 (25/64")
JS325-200L	200 ( 7-7/8" )	170 (6-11/16")	*50 (1-31/32")	50 (1-31/32")	36.5 ( 1-7/16" )	13.5 (17/32")

Item No.	F	F <sub>1</sub>	G	L	M	M <sub>1</sub>	t <sub>1</sub>	t <sub>2</sub>	Weight (kg)
JS325-100L	16 ( 5/8" )	25 (63/64")	10 (25/64")	60 (2-23/64")	27 (1-1/16")	M16 ( 5/8" )	10.5 (13/32")	10 (25/64")	0.7
JS325-150L	20 (25/32")	40 (37/64")		75 (2-61/64")	30 (1-3/16")	M20 (25/32")	12.0 (15/32")	13 (33/64")	4.9
JS325-200L	25 (63/64")		15 (19/32")	86 (3-25/64")		M24 (15/16")	14.0 (35/64")	10 (25/64")	9.4