LAMP

DOOR STOPPER

Installation

Fixed glass

Fixed glass

Hinge

Swing doo

- 7

w/o boring

HT-G70




Features

- For use on single swing glass doors.
- No need for glass processing. Simply press the packing (PVC material) onto the glass to fix it in place.
- · Can be used in areas with frequent contact to water including shower booths.

Remarks

- Do not use in upper glass transom.
- · Soft-closing hinges/self-closing (function within final 25 degrees) hinges are recommended to use with to prevent from excessive impact.



	No.	Part N	lame	Material		Finish/Colour	
	0	Body Pad Gasket		Stainless Steel (SC	Mirror Natural Clear		
	2			Silicone (Si)			
	3			Vinyl Chloride Resin (PVC)			
	(4)	Screw		Stainless Steel (SUS303)		Plain	
Item Code	Item Na	m Name		Glass Thickness		ght	Carton
270-021-701	HT-G7	HT-G70		8, 10, 12		a	40 pcs

STEEL

MI, MBR

DOOR STOPPER

Swing door



Cut Out Dimensions

10

Swing door


5

w/ boring

R100

Fixed glass

Fixed gla



Features

- Holds door open with a powerful magnet.
- · Floor mounted or wall mounted.
- No need to crouch down and latch the door stopper to hold door open.
- Body is ball shaped, allowing for a firm hold even if alignment is slightly off.
- Parts Included
- Rounded head wood screw 3.5×22 (Body)
- Rounded head wood screw 3.1×16 (Mounting plate)

Sold Separately

Anchor bolt MA (below)

Anchor bolt MA (Sold Separately)

-35-Floor-mount			Item Code	Item Name	Weight	Box	Carton	
5			270-050-100	MA	114 g	25 pc	s 100 pcs	
Item Name	Colour	Magnet	ic Force	Weight	Box		Carton	
MI	lvory	137 N	14 kgf	165 g	10 pcs		100 pcs	
MBR	Brown	137 N	14 kgf	165 g	10 pcs		100 pcs	



Item Code 270-172-008 270-172-007