TORQUE HINGES

DAMPER

HINGES

DETENT HINGES

CONCEALED HINGES

BUTT

PIANO

STEP

LIFT-OFF

HINGES

HINGES

PIVOT

HINGES

SPRING

HINGES

CLEAN ROOM HINGES

HINGES FOR ALUMINIUM FRAME

DROP

HINGES GLASS DOOR HINGES SPECIAL

HINGES

HINGES

HINGES

LIFT ASSIST HINGES

DETENT HINGE HG-FH128









[How to Install (Screws Included)]

Cover not shown



Install by steps (A)~ (C)

[How to Adjust Position (With Cover Removed)]



• Holds doors at 60° and 120°.

- Depth and horizontal adjustment can also be made after installation.
- Covers for the screw holes are included.
- Fluororesin washer at rotation part ensures smooth operation.

[Applications]

Environmental test equipment, laboratory equipment, etc.

[Parts Included]


- ■Hexagon socket head cap screw M6×25 (SUS)
- Hexagon socket head cap screw M5×25 (SUS)
- Hexagon socket countersunk head screw M5×14 (SUS)
- Oval washer for M5 (SUS)
- Washer 6 (SUS)








Horizontal adjustment





Depth adjustment



Horizontal adjustment of door can be made by rotating the cabinet-side bolt of hinge.

Depth adjustment of door can be made by rotating the door-side bolt of hinge.





No.	Part Name	Material	Finish		
1	Body A		Dull Nickel + Clear Finish		
2	Body B	Zinc Alloy (ZDC)	Duli Nickei + Clear Finish		
3	Bracket A		Nickel		
4	Bracket B	Stainless Steel (SUS304)	Barrel Polished		
5		PTFE			
6	Washer	POM	_		
7		PS			
8	Cover	AES	Metallic Silver Paint		

No.	Part Name	Material	Finish
9	Hexagon Socket Countersunk Head Screw M5 x 25		
10	Hexagon Socket Head Cap Screw M5 x 12		_
11)	Washers 6		
12)	Oval Washer for M5	Ctainlana	
(13)	Spring Pin 4 x 32	Stainless Steel	
(14)	Hexagon Socket Countersunk Head Screw M5 x 14		
(15)	Hexagon Socket Head Cap Screw M5 x 25		
16)	Hexagon Socket Head Cap Screw M6 x 25		
(17)	Hexagon Socket Low Head Screw M5 x 30		

RoHS	CAD	Item Code	Item Name	Door Width	Door Height	Door Weight kg/Pair	Retaining Torque N·m/Pair	Retaining Torque kgf·m/Pair	Weight (g)	Box (pcs)	Carton (pcs)
G	30	170-090-317	HG-FH128	600~900	900~1200	Max. 40	10	102	1500	1	6