DAMPER HINGE HG-JH







• Hinge with built-in dampers hinge UDH 1.

Smooth movement in the opening direction.

Left-handed...Damper works when rotating counterclockwise. Right-handed...Damper works when rotating clockwise.

AS parts set for installing to aluminium frame also available.

(S) election Tool

Sasuga-kun

Applicable Products

Used for Product

Available on Web!

Selection &

Simulation.

[Applications]

Top-opening lids and upper covers of various cabinets. [Remarks]

- Be sure to read the "Cautions"
 3
- Torque range is the value when using two hinges for one door.
- Install a stopper such as a stay at the lid opening/closing position (0~115 degree or less) for not exceeding the specified rotation range.
- When installing, ensure that both hinge shafts are levelled and aligned.
- Sold in pairs.

HINGES

HINGES LIFT

ASSIST HINGES

DETENT HINGES

CONCEALED HINGES

BUTT HINGES

PIANO HINGES

STEP HINGES

LIFT-OFF HINGES

PIVOT HINGES

SPRING HINGES

CLEAN ROOM HINGES

HINGES FOR ALUMINIUM FRAME


DROP HINGES

GLASS DOOR HINGES

SPECIAL HINGES


[Installation]


Sold in pairs.




Shaft (white: left-handed) Shaft (grey: right-handed)

When viewing door from lower side as shown above, install the left-handed type damper (white) on the left side and the right-handed type (grey) on the right side.







No.	Part Name	Material	Finish / Colour		
1	Bracket	PBT			
2	Damper	РВІ	Emboss/Dark Grey		
(3)	Can	PP			

RoHS	CAD	Item Code	Item Name	Torque N·m/pair	Torque kgf·cm/pair	Marking Colour (Base Side)	Weight (g)	Box (pairs)	Carton (pairs)
G'	3D	170-092-209	HG-JH25	3~5	30.6~51	Blue	200	4	64
G	3D	170-092-210	HG-JH35	5~7	51~71.4	Red	193	4	64

Refer to 1 : P.66, 2 : P.53, 3 : P.15

