


RAISED COUNTER BRACKET CTB65-PMS60-240 60°/Top-mounted/Front-screw





- Allows for additional floating countertops, expanding your counter space.
- Designed to allow cables to be put through. (Max. diameter: ϕ 10.5)

[Applications]


Commercial reception counters, kitchens, serving bars, and more.

[Remarks]

- Please make sure the support structure that the bracket will be attached to is strong enough to handle the load.
- Max. pitch of adjoining brackets is 900 mm.
- Max. size of countertop overhung is 1,000 mm in width and 400 mm in depth. (when using two brackets)
- Min. thickness of both countertops is 20 mm.

[Remarks]

■Countersunk tapping screw M5×20




RoHS CAD	Item Code	Item Name	Angle	Mount	Screw	Colour Finish	Material	Load Capacity N /pc	Load Capacity kgf /pc	Weight (g)	Box	Carton
G 2030	120-041-442	CTB65-PMS60-240-SL	60°	Top- mounted	Front	Stainless Steel	Aluminium Alloy	600	61.2	570	1 pc	10 pcs
G" 203D	120-041-443	CTB65-PMS60-240-BL				Black					1 pc	10 pcs
G" 2030	120-041-444	CTB65-PMS60-240-WT				White					1 pc	10 pcs

RAISED COUNTER BRACKET CTB65-PM60-170 60°/Top-mounted/Back-screw



[Installation]



- Allows for additional floating countertops, expanding your counter space.
- Designed to allow cables to be put through. (Max. diameter: φ 10.5)

[Applications]

Commercial reception counters, kitchens, serving bars, and more.


[Remarks]

- Please make sure the support structure that the bracket will be attached to is strong enough to handle the load.
- Max. pitch of adjoining brackets is 900 mm.
- Max. size of coutertop overhung is 1,000 mm in width and 400 mm in depth.
 (when using two brackets)
- Min. thickness of a countertop overhung is 20 mm.

Min. thickness of a countertop that will support additional countertop is 30 mm.

[Parts Included]

- Countersunk tapping screw M5×20
- ●Hex head bolt M6×45
- Washer 6
- Spring washer 6



RoHS	CAD	Item Code	Item Name	Angle	Mount	Screw	Colour Finish	Material	Load Capacity N /pc	Load Capacity kgf /pc	Weight (g)	Box	Carton
G	20 <mark>30</mark>	120-041-433	CTB65-PM60-170-SL	60°	Top- mounted	Back	Stainless Steel	- Aluminium - Alloy	600	61.2	450	1 pc	10 pcs
G'	20 <mark>30</mark>	120-041-434	CTB65-PM60-170-BL				Black					1 pc	10 pcs
G	20 <mark>30</mark>	120-041-435	CTB65-PM60-170-WT				White					1 pc	10 pcs

