

LATCH W/ INDICATOR With Door Stopper





ET-70DN



Screw and Spacer Recommended

	Inward opening						Outward opening					
Door Thickness	13			16			13			16		
Side board thickness	13	16	20	13	16	20	13	16	20	13	16	20
Hexagon top bolt (2pcs)	M5×	M5×	M5×	M5×	M5×	M5×	M5×	M5×	M5×	M5×	M5×	M5×
nexagon top boil (2pcs)	45	45	50	45	50	55	45	45	50	45	50	55
ET-7 spacer	0	0	0	0	0	0	0	0	1	0	0	1
ET-3 spacer	0	0	0	1	1	1	0	1	0	0	1	0
Hexagon socket button	M4×	M4×	M4×	M4×	M4×	M4×	M4×	M4×	M4×	M4×	M4×	M4×
head screw	10	10	10	10	10	10	10	10	16	10	10	16

^{*}When using with the door stopper, please use with M4 washer as well.

Please contact us for other information.

Features

Overlapped door application.

Remarks

Please use a spacer according to the door thickness.

Parts Included

Hex key Door stopper

Option


Spacer: ET-3, ET-7






ET-125T

Cut Out Dimensions





*Installation position:

- Inward opening : Door - Outward opening : Side Board

Body

Item Code	Item Name	Door/Panel Thickness	Material	Finish	Weight	Box	Carton
140-180-546	ET-70DN	Door : 13, 16 Side Panel: 13, 16, 20	Stainless Steel (SUS304)	Satin	371 g	1 pc	50 pcs

Spacer (Sold Separately)

Item Code	Item Name	Material	Colour Thickness		Weight	Box	Carton	
140-180-975	ET-3	ABS	Black	3	14 g	25 pcs	750 pcs	
140-172-566	ET-7	ABS	Black	7	18 g	15 pcs	750 pcs	

LATCH W/ INDICATOR



Features

- For sliding door applications.
- Large handle for easy operation.

Parts Included

Hex key

Cut Out Dimensions

