56 82

13 + +

466

HINGES

GRAVITY HINGE


Spacer ET-100AFR (Included) Outside 3||-2.5 26 Outside (14) 69 (min.) e pane Ļ Inside ė 13 ET-100AFR ET-100ADR Inside 4×¢5.2 Cut Out Dimensions (At closed position) ET-100ADR ET-100AFR -56 56 -90--96--4×¢8.5 4×08.5 Side Side panel Doc 0 Ð Ð 0 for self-closing setting 6 for self-opening setting 0 for self-closing ng 6 for self-opening Body etting Item Code Item Name Type Finish Weight Box Material 170-099-066 ET-100AFR Right Stainless Steel (SUS304) Satin 955 g 10 sets 170-099-067 ET-100AFL Left Stainless Steel (SUS304) Satin 955 g 10 sets 170-099-905 ET-100ADR Right Stainless Steel (SUS304) Satin 980 g 10 sets

170-099-048 ET-100ADL Left Stainless Steel (SUS304) Satin 980 g 10 sets

GRAVITY HINGE

Out Dimensions

sed position)



Recommended Screw Hexagon top bolt

Door Thickness		Side Panel Thickness			
13	16	13	16	20	
M5×10	M5×12	M5×10	M5×12	M5×16	

Item Code	Item Name	Туре	Material Finish		Weight	Box
170-099-906	ET-100BFR	Right	Stainless Steel (SUS304)	Satin	956 g	10 sets
170-099-049	ET-100BFL	Left	Stainless Steel (SUS304)	Satin	956 g	10 sets

SUGATSUNE

Features

• For inward opening doors. Can be installed with door flush or with an offset.

STAINLESS 304 STEEL

- The automatic closing radius of the door can be adjusted by angles of 18° (Must be adjusted during installation)
- Door rises up to 6mm at a radius of 90°.

Remarks

3 pcs in 1 set required for 1 door.

Parts Included

Spacer

Option

Spacer, ET-100-S13 to double the gap between door and side panel.

Recommended Screw

Hexagon top bolt

Туре	Spacer	Door Thickness		Side Panel Thickness		
Type		13	16	13	16	20
ET-100AF	-	M5×10	M5×12	M5×10	M5×12	M5×16
ET-100AD	Parts Included	M5×10	M5×12	M5×14	M5×16	M5×20
	Option (ET-100-S13)	M5×10	M5×12	M5×20	M5×25	M5×25

Spacer for ET-100AD (Sold Separately)

Item Code	Item Name	Weight	Box
170-020-997	ET-100-S13	16 g	900 pcs



304 STEEL

• For outward opening doors. Can be installed with door flush or with an offset.

- The automatic closing radius of the door can be adjusted by angles of 18°
- (Must be adjusted during installation)
- Door rises up to 6mm at a radius of 90°.

Remarks

Features

3 pcs in 1 set required for 1 door.

Outside	Cut C (At close



