

LAMP. EXCELOCK. STRIKE PLATE FOR GLASS DOOR XL-ESG

For Swing Door







• It perfectly matches style when used in combination with the glass hinge XL-GC04-CR


[Features]


The door needs to be properly closed for the lock to engage. We recommend the use of a door stopper or magnetic catch.


[Parts Included]

Installation adjustment spacer

[Installation]







[Glass Cut Out Dimensions] -45 This diagram shows the right door

XL-ESG-R is shown. XL-ESG-L is symmetrically opposite.

RoHS	CAD	Item Code	Item Name	Specification	Material	Finish	Max. Door Width	Max. Door Height	Glass Thickness
=	2D3D	150-022-211	XL-ESG-R	Right	Zinc Alloy (ZDC)	Chrome	500	1200	5, 6, 8
_	2D <mark>3D</mark>	150-022-210	XL-ESG-L	Left					

Refer to 1: No.240A P.449, 2: P.E13

LAMP. EXCELOCK® STRIKE PLATE FOR WOOD DOOR XL-ESW











• It can be used with both a swing door and a slide door.

[Features]

• The door needs to be properly closed for the lock to engage. We recommend the use of a stopper or door guide for sliding doors, and a door stopper or magnetic catch for hinged doors.


[Parts Included]


Cross-hole pan-head tapping screw 4×16


[Sold Separately]


Lock unit XL-ELU


[Installation]











RoH:	CAD	Item Code	Item Name	Material	Finish	Colour	Max. Width/Slide door	Max. Width/Swing door	Max. Height
_	20 <mark>30</mark>	150-023-021	XL-ESW-R	Stainless Steel (SUS304) / ABS resin	Barrel Polishing	Black	800	500	1200
Ξ	2D <mark>3D</mark>	150-022-212	XL-ESW-L						



