HINGES

SELECTION **GUIDE**

HES CONCEALED

CONCEALED

HINGES

HINGES

DAMPER HINGES

TORQUE HINGES

GLASS

HINGES

PIVOT

HINGES

TABLETOP HINGES

DETENT

HINGES

BUTT

HINGES

LIFT-OFF

HINGES

PIANO HINGES

SPRING HINGES

ANGLE

HINGES

GRAVITY HINGES

LAMP, 3-WAY ADJUSTABLE CONCEALED HINGE HES3D-H120-36 Centre Door Mortise NEW










Passed Private 300K Cycle Test



KIDS DESIGN AWARD 2021










Feature

HES Hinge



| No. | Part Name | Material | Finish/Colour | | | | |
|-----|-----------------------------------|-------------------|---------------|-------------------|-------|--|--|
| | | Waterial | DC | DN | BL | | |
| 1 | Body | Zinc Alloy (ZDC) | Satin | Satin | Black | | |
| (2) | Base Frame | ZITIC ATIOY (ZDC) | Chrome | Nickel | | | |
| 3 | Shaft | Stainless Steel | - | - | - | | |
| 4 | Screw Cover (Door side: 2 pcs) | ABS | Silver | Champagne Gold | Black | | |

For a 36mm thick door, the mortise is centred and allows it to function as either a left or right-handed door.

· Has increased load capacity of 50 kg with two hinges.

- Thin profile (21mm) allows for shallow mortise.
- 3D Adjustment Post Installation: Adjust vertically, horizontally, and
- For simplified door hanging, the hinge divides into two parts: one for the door-side and one for the jamb-side.
- Can temporarily be hung before fixing with screws.

INSTRUCTION SCREW

Applications

Interior doors


Parts Included

- Cross-recessed countersunk tapping screw 5 x 20 (4 pcs / hinge) stainless steel
- Hex kev 3
- Cutout template

Sold Seperately

HES3D-120-JIG (installation jig)


- Read all remarks on handling thoroughly before use.
- Please use the Selection Tool for HES Concealed Hinges to select a hinge.
- When use with a door damper, the following dampers are recommended:
- LDD-S (P.566)
- LDD-V (P.568)
- LDD-V100 (P.570)
- LDC-N2 (P.572)
- * Each door damper has different load capacity. Please check that before use.
- Required number of hinges also depends on door stiffness and warpage. Please check actual conditions and performance before use.



| Door | | Jamb | | | |
|---------------------|---------------|---------------------|---------------|--|--|
| Y: Machining Margin | B: Chamfering | X: Machining Margin | A: Chamfering | | |
| | 1 | Max. 5 | 1 | | |
| Max. 4 | | 6 | 2 | | |
| | | 7 | 0 | | |
| 5 | 3 | Max. 5 | 3 | | |

The table shows how much margin and chamfering are required for the door to open properly.

Cut Out Dimensions



Please drill prepared holes for the tapping screws.

| Hinge surface Surface Please drill prepared holes for the tapping screws. | | | | | | | | | | | | |
|---|-----------------|----------------|-------------|--------------|---------------|---------|-----------|---------|-----------|--------|-------|-------|
| Item Code | Item Name | Colour | Door Specs | | Load Capacity | | | Opening | Box | Carton | | |
| item code | item Name | Colour | Width | Height | Thickness | N/2 pcs | kgf/2 pcs | N/3 pcs | kgf/3 pcs | Angle | (pcs) | (pcs) |
| 170-047-861 | HES3D-H120-36DC | Silver | | | | | | | | | | |
| 170-047-862 | HES3D-H120-36DN | Champagne Gold | Max. 900 | Max. 2700 | Min. 34 | 490 | 50 | 637 | 65 | 180° | 2 | 24 |
| 170-047-863 | HES3D-H120-36BL | Black | 000 | 2,00 | 0. | | | | | | | |

Installation Jig sold separately

| Item Code | e Item Name Material | | Colour | Colour Weight (g) | | Carton (pcs) | | |
|-------------|----------------------|-----|--------|-------------------|-----|--------------|--|--|
| 170-044-186 | HES3D-120-JIG | РОМ | Red | 4 | 100 | 400 | | |

+2 mm