

 QUICK LINK DFKA-7350


- Made from highly corrosion-resistant SUS316, designed for high-load applications.
- Turn the nut to open and close.


SUS

Application

- Connecting chains and wire ropes, and terminal fittings.

Remarks

- Be sure to read the "Cautions regarding shackles, carabiners, and ring catches".



RoHS	Item Code	Item Name	Material	L	S	D	Load Capacity N	Load Capacity kgf	Weight (g)
●	110-056-536	DFKA-7350-4	Stainless Steel (SUS316)	40	5.5	4	630	64	12.5
●	110-056-537	DFKA-7350-6		58	7.5	6	1860	190	32.5
●	110-056-538	DFKA-7350-8		75	10.5	8	4310	439	75
●	110-056-539	DFKA-7350-10		90	12.5	10	8570	874	130
●	110-056-540	DFKA-7350-12		107	14.5	12	11000	1122	225

Refer to : P/F20

*This is the load capacity in the longitudinal direction.

 SWIVEL PULLEY BLOCK DFMB-314


- Made from highly corrosion-resistant SUS316, designed for high-load applications.
- 360° free rotating eye.


SUS

Application

- Yacht, boat, factory.

Remarks

- Be sure to read the "Cautions regarding shackles, carabiners, and ring catches".



DFMB-314-20 shown.

RoHS	Item Code	Item Name	Material	L ₁	L ₂	A	B	C	Max Rope Dia.	Load Capacity N	Load Capacity kgf	Weight (g)
●	110-056-122	DFMB-314-20	Stainless	76	19	13.5	25	4.8	φ6	490	50	60
●	110-056-123	DFMB-314-25	Steel	81	21	15	30	5.9	φ9	730	75	115
●	110-056-124	DFMB-314-32	(SUS316)	98			36		φ10	1170	120	171

Refer to : P/F20