

# Spring plunger

## FSTIm M3-IG 4/2.5 L 5

<https://www.schmalz.com/10.01.02.01334>



Part no.: 10.01.02.01334


Homepage > Vacuum Technology for Automation > Vacuum Components > Mounting Elements > Spring plungers > Spring Plungers FSTIm > FSTIm M3-IG 4/2.5 L 5

## Spring plunger with internal damping spring and height compensation



Suction cup connection: M3-F  
Vacuum connection: Hose 4/2.5  
Shape: n.d.  
Spring stroke Z: 5 mm

### Design Data



Attribute	Value
-----------	-------

B	21.5 mm
dn	1.8 mm
D	2.5 mm
G2	M3-F
G3	M10x1-M
H	35 mm
H2	14 mm
LG2	4.5 mm
LG3	19 mm
SW1	14 mm
SW2	13 mm
Z	5 mm

### Contact to Schmalz

J. Schmalz GmbH | Johannes-Schmalz-Straße, 72293 Glatten, Deutschland | +49 7443 2403-102 | [customercenter@schmalz.de](mailto:customercenter@schmalz.de)


## Technical Data

Attribute	Value
Spring rate	0.055 N/mm
Spring pretension	0.5 N
Spring force, centre	0.64 N
Vertical load	15 N
Horizontal load	1.5 N
Weight	15.5 g
Ambient temperature	0 ... 80 °C

### Note:

- Spring force: Referred to 50 % of operating stroke
- Vertical load: Maximum static loading
- Horizontal load: The specification of the horizontal load refers to the lower edge of the plunger with extended spring. It is a maximum static stress and it impairs the spring compression and extension in horizontal position.

## Accessories



### VSL 4-2.5 PU SO

Part no. 10.07.09.00142

Hose for vacuum and compressed-air systems

External diameter D: 4 mm

Internal diameter d: 2.5 mm

Length (max): 50 m

Material: PU

Installation radius (min): 8 mm

Colour: blue

Pressure range (operating pressure):

0.00 ... 6.00 bar

Ambient temperature: -25 ... 60 °C

SO: Hose in soft design

### Contact to Schmalz

**ST M5-AG 2.5 MS-V**

Part no. 10.08.03.00312

Hose sleeve

Thread G1: M5-M

Internal hose diameter: 2.5 mm

Material: Brass

Surface: nickel plated

**HTR-STA 47 1N D10/16 FL**

Part no. 10.08.03.00085

Holder for flexible mounting of suction cups/spring plungers on sections

Length L: 47 mm

Cross-beam connection: Sliding block

Suction cup or spring plunger conn.:

Contour D10 and D16

Shape: flat

**HTR-STS 30x30 D10/16 WI**

Part no. 10.08.03.00088

Holder for flexible mounting of suction cups/spring plungers on square tubes

Cross-beam connection: 30x30

Suction cup or spring plunger conn.:

Contour D10 and D16

Shape: angled



**HTR-ST5 40x40 D10/16 WI**

Part no. 10.08.03.00089

Holder for flexible mounting of suction cups/spring plungers on square tubes

Cross-beam connection: 40x40

Suction cup or spring plunger conn.:

Contour D10 and D16

Shape: angled