

# Spring plunger

## FSTIm M5-IG 6/4 A 20 VG

<https://www.schmalz.com/10.01.02.01293>



Part no.: 10.01.02.01293


Homepage > Vacuum Technology for Automation > Vacuum Components > Mounting Elements > Spring plungers > FSTIm M5-IG 6/4 A 20 VG

### Spring plunger with internal damping spring and height compensation



Suction cup connection: M5-F  
Vacuum connection: Hose 6/4  
Shape: n.d.  
Spring stroke Z: 20 mm  
Shape: With rotation lock

#### Design Data



Attribute	Value
dn	2 mm
D	4 mm
G2	M5-F
G3	M10x1-M
H	79.7 mm
H2	29 mm
LG2	4.5 mm
LG3	41 mm
SW1	14 mm
SW2	8 mm
Z	20 mm


#### Contact to Schmalz

J. Schmalz GmbH | Johannes-Schmalz-Straße, 72293 Glatten, Deutschland | +49 7443 2403-102 | [customercenter@schmalz.de](mailto:customercenter@schmalz.de)

## Technical Data

Attribute	Value
Shape	With rotation lock
Spring rate	0.052 N/mm
Spring pretension	0.5 N
Spring force, centre	1.02 N
Vertical load	15 N
Horizontal load	1.5 N
Weight	21 g
Ambient temperature	0 ... 80 °C

## Accessories



### VSL 6-4 PU SO

Part no. 10.07.09.00141

Hose for vacuum and compressed-air systems

External diameter D: 6 mm

Internal diameter d: 4 mm

Length (max): 50 m

Material: PU

Installation radius (min): 15 mm

Colour: blue

Pressure range (operating pressure):

0.00 ... 6.00 bar

Ambient temperature: -25 ... 60 °C

SO: Hose in soft design

## Contact to Schmalz



**HTR-STA 47 1N D10/16 FL**

Part no. 10.08.03.00085

Holder for flexible mounting of suction cups/spring plungers on sections

Length L: 47 mm

Cross-beam connection: Sliding block

Suction cup or spring plunger conn.:

Contour D10 and D16

Shape: flat



**HTR-STS 30x30 D10/16 WI**

Part no. 10.08.03.00088

Holder for flexible mounting of suction cups/spring plungers on square tubes

Cross-beam connection: 30x30

Suction cup or spring plunger conn.:

Contour D10 and D16

Shape: angled



**HTR-STS 40x40 D10/16 WI**

Part no. 10.08.03.00089

Holder for flexible mounting of suction cups/spring plungers on square tubes

Cross-beam connection: 40x40

Suction cup or spring plunger conn.:

Contour D10 and D16

Shape: angled