

# Tooling-System- Schmalz-Ejektor

## SEAC 10 ECO

<https://www.schmalz.com/10.02.02.03702>



Part no.: 10.02.02.03702

Homepage > Vacuum Technology for Automation > Vacuum Components > Vacuum Generators > Decentralized Ejectors > Ejectors with Atmospheric Ventilation SEAC ECO > SEAC 10 ECO

## Tooling-System-Schmalz-Ejektor



Nozzle size: 1,0 mm  
with: atmospheric release  
Pressure range (operating pressure):  
4.0 ... 6.0 bar

## Design Data



Attribute	Value
-----------	-------

B	28.5 mm
---	---------

B3	16.1 mm
----	---------

D	27 mm
---	-------

G1	G1/8"-F
----	---------

H	24 mm
---	-------

L	46 mm
---	-------

L1	77.5 mm
----	---------

L3	6 mm
----	------

X1	28 mm
----	-------

## Contact to Schmalz

J. Schmalz GmbH | Johannes-Schmalz-Straße, 72293 Glatten, Deutschland | +49 7443 2403-102 | [customercenter@schmalz.de](mailto:customercenter@schmalz.de)

## Technical Data

Attribute	Value
Nozzle size	1 mm
Degree of evacuation	85 %
Suction rate (max)	2.1 m <sup>3</sup> /h
Suction rate (max)	35 l/min
Air consumption (during evac.)	52 l/min
Pressure range (operating pressure)	4.0 ... 6.0 bar
Weight	95 g
Pressure range (operating pressure)	58.0 ... 87.0 psi
Suction rate (max)	1.235 cfm
Air consumption (during evac.)	1.836 cfm
Vacuum (max)	25.1 inHg

### Note:

- Air consumption: At optimal operating pressure (4,5 bar)
- 
-