

Schmalz X-Pump

SXMPi 25 IMP Q PC 2xM12-5

<https://www.schmalz.com/10.02.02.04563>



Part no.: 10.02.02.04563

Homepage > Vacuum Technology for Automation > Vacuum Components > Vacuum Generators > Compact Ejectors > Compact Ejectors X-Pump
SXPI / SXMPi with IO-Link > SXMPi 25 IMP Q PC 2xM12-5

Compact ejector with Condition Monitoring, power blow-off function and pneu. air-saving function



Nozzle size: 2,5 mm
Control: Double pilot valve
Pneum. Connection: Quick Change
with: Pressure Control
Electrical connection:
2xConnect M12, 5+5 pol
Suction rate (max): 185 l/min
Air consumption (during evac.):
290 l/min
Communication: IO-Link (Class A)
Vacuum (max): -850 mbar
Noise level (free): 67 dB
Protection: IP 65

Design Data



Attribute	Value
-----------	-------

B	39 mm
---	-------

d	5.5 mm
---	--------

G2	M12x1-M
----	---------

H	146 mm
---	--------

H1	160 mm
----	--------

H2	54 mm
----	-------

H3	6 mm
----	------

L	210 mm
---	--------

L2	5 mm
----	------

Contact to Schmalz

J. Schmalz GmbH | Johannes-Schmalz-Straße, 72293 Glatten, Deutschland | +49 7443 2403-102 | customercenter@schmalz.de

Attribute	Value
L3	97 mm
X1	89 mm
Y1	10 mm

Technical Data

Attribute	Value
Nozzle size	2.5 mm
Degree of evacuation	85 %
Suction rate (max)	185 l/min
Suction rate (max)	11.1 m ³ /h
Air consumption (during evac.)	290 l/min
Air consumption (during evac.)	17.4 m ³ /h
Air consumption (blow off) (max)	320 l/min
Vacuum (max)	-850 mbar
Noise level (free)	67 dB
Pressure range (operating pressure)	3.0 ... 6.0 bar
Int. hose diameter (recom.) comp.-air	8 mm
Int. hose diameter (recom.) vacuum side	9 mm
Weight	0.96 kg
Ambient temperature	0 ... 50 °C
Pressure range (operating pressure)	43.5 ... 87.0 psi
Suction rate (max)	6.533 cfm
Air consumption (during evac.)	10.241 cfm
Vacuum (max)	-25.1 inHg
Product family	SXMPi

Contact to Schmalz

Note:

- The supply voltage for vacuum switches and solenoid valves is 24V DC
 - Air consumption: At optimal operating pressure
 - Hose diameter: For max. length 2 m
-
-