


Homepage > Vacuum Technology for Automation > Vacuum Components > Switches and System Monitoring > Electronic Vacuum/Pressure
Switches > Vacuum and Pressure Switches VSi > VSi P10 D M12-4

Vacuum and pressure switch with two digital output signals and IO-Link function



Measuring range: 0...10 bar
Type: with display
Electrical connection:
Male connect M12, 4 pol
Indication: 2xLED
Protection: IP 65

Design Data



Attribute	Value
-----------	-------

D	19.6 mm
G1	G1/8"-M
G2	M5-F
G3	M12x1-M
L	60.5 mm
L1	78.5 mm
LG1	8 mm

Technical Data

Attribute	Value
Type	with display

Attribute	Value
Measured medium	Non-aggressive gases; dry, oil-free air
Measuring range	0.0 ... 10.0 bar
Overpressure resistance	15 bar
Repeatability	± 3% of full-scale value
Hysteresis	Adjustable
Inputs/outputs	2 digital
Switching capacity (max)	100 mA
Indication	2xLED
Electrical connection	Male connect M12, 4 pol
Connection	G1/8"-M + M5-F
Voltage	10-30V DC
Current consumption	35 mA
Protection	IP 65
Temperature influence	± 3% of full-scale value
Ambient temperature	0 ... 50 °C
Weight	16 g
Measuring range	0.0 ... 145.0 psi
Overpressure resistance	217.55 psi

Accessories

Contact to Schmalz

J. Schmalz GmbH | Johannes-Schmalz-Straße, 72293 Glatten, Deutschland | +49 7443 2403-102 | customercenter@schmalz.de



ASK B-M12-4 5000 K-4P

Part no. 21.04.05.00263

Connection cable

Interface Connection 1:

Fem connect M12, 4 pol

Cable length: 5000 mm

Interface Connection 2: Cable 4

Material: PUR-Cable



BEF-WIN 18x22x59 1 VS

Part no. 10.06.02.00061

Mounting bracket

Width B: 18 mm

Height H: 22 mm

Length L: 59 mm

Wall thickness s: 1 mm

for: Vacuum switch